PFISTERER
Your Power Connection

Voltage detector KP-Test 5R+ 11 kV for Catenaries, Two-Parts

The **KP-Test 5R+ 11 kV 16,7 Hz** capacitive voltage detector is designed for use on railway catenaries. It indicates the presence of operating voltage when brought into contact with the conductor.



Picture may vary.

Technical Description:

- Bright LEDs for clear recognition
- Particularly loud, integrated audible signal
- Extensive self-test functions at switch-on
- Contact electrode in hook form with contact pin for optimum contact with the catenary
- For single-phase networks
- New, simple and intuitive to use plug-in system with a large, blue, easy-to-use push button
- Consistent colouring of fibre glass tube in yellow

The **KP-Test 5R+ 11 kV 16,7 Hz** is built in accordance to DIN VDE 0681, Part 6.

Versions in other languages or with other signal mode are available on request.

Technical Data

Article no.		**930 310 002 00006**
Nominal voltage	**U_n (kV)**	**11**
Nominal frequency	**f_N (Hz)**	**16.7**
Suitable bag		**B22**
Carrying bag included		**no**
Voltage type		**AC**
Area of application		**Catenary Wires**
Type of device		**complete**
Language on labels		**de**

© 2026 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications

Technical Data

Article no.		930 310 002 00006
Type		KP-Test 5R+

Dimensions

Total length	L_G (mm)	4795
Length of handle	L_H (mm)	1500
Insulating length	L_I (mm)	1071
Transporting length	L_T (mm)	2440
Diameter of insulating element	d (mm)	33

© 2026 PFISTERER Kontaktsysteme GmbH www.pfisterer.com We accept no liability for printing errors / Subject to technical modifications